

# MSDS

Material Safety Data Sheet

revised 09-20-2008

## Premier Hot Melt Tapes

### I. PRODUCT IDENTIFICATION

Name: Carpet Seam Tape  
Class: Thermoplastic Carpet Seam Tape  
Emergency Telephone CHEMTREC:  
800-424-9300

### II. HMIS (0 = minimal hazard; 4 = severe)

Health = 0 Flammability = 1 Reactivity = 0

### III. HAZARDOUS INGREDIENTS

None per OSHA Regulation:  
29CFR1910.1200 None per SARA Title III,  
Section 313 and TSCA 40 CRF 372

### IV. PHYSICAL DATA

MELTING POINT: 230°F; BOILING POINT:  
Not established; ODOR: Neutral; SPECIFIC  
GRAVITY: 0.98; VAPOR PRESSURE: Not  
established; VAPOR DENSITY: Not  
established

### V. FIRE & EXPLOSION HAZARD DATA

FLASH POINT: NA; AUTOIGNITION TEM-  
PERATURE: Not established; LOWER  
EXPLOSIVE LIMIT: Not established;  
UPPER EXPLOSIVE LIMIT: Not estab-  
lished; EXTINGUISHING MEDIA: A solid  
stream of water may scatter molten prod-  
uct. UNUSUAL FIRE AND EXPLOSION  
HAZARDS: Material will burn in a fire.  
SPECIAL FIRE FIGHTING PROCEDURES:  
Persons exposed to products of combus-  
tion should wear self-contained breathing  
apparatus and full protective equipment.  
HAZARDOUS COMBUSTION PRODUCTS:  
Carbon dioxide, Carbon monoxide

### VI. HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: Inhalation,  
Ingestion, skin and eye contact. EFFECTS  
OF OVEREXPOSURE: Eyes - No irritation  
hazard in normal industrial use. Exposure  
to hot material may cause thermal burns.  
Skin - Skin contact at room temperature is  
not irritating. Contact with product at  
elevated temperatures can result in  
thermal burns. Inhalation - No irritation  
hazard in normal industrial use. Ingestion  
- Ingestion is not an anticipated route of  
exposure.

### VII. FIRST AID MEASURES

EYE CONTACT: Use an eye wash to  
remove a chemical from your eye regard-  
less of the level of hazard. Flush eye with  
water for 15 minutes. Get medical atten-  
tion. SKIN CONTACT: Wash affected  
area(s) thoroughly with soap and water.  
For hot material, immediately immerse in  
or flush the affected are with large  
amounts of cold water to dissipate heat.  
cover with clean gauze and do not attempt  
to remove the material yourself. Seek  
medical attention. Medical personnel: coat  
with mineral oil to soften material for  
removal. INHALATION: This material does  
not present a hazard if inhaled. Remove to  
fresh air if necessary. INGESTION: No  
hazard in normal industrial use. Do not  
induce vomiting. Seek medical attention if  
symptoms develop.

### VIII. SPILL OR LEAK PROCEDURES

SPECIAL PROTECTION: No adverse health  
effects expected from the clean-up of  
spilled material. CLEAN-UP: Allow molten  
material to solidify before disposal.


### IX. PROTECTIVE EQUIPMENT

No safety equipment required other than  
goggles.

### X. SPECIAL PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN

Premier believes that data set forth herein  
is accurate as of the date hereof, and  
makes no warranty with respect thereto  
and expressly disclaims all liability for  
reliance thereon. Such data are offered  
solely for your consideration, investigation  
and verification.



**PREMIER FLOORING PRODUCTS**

www.premiertapeproducts.com  
premier@premierapeproducts.com

**TRAXX**  
CORPORATION

1201 E. Lexington Ave • Pomona, CA 91766 • phone: 909-623-8032 • fax: 909-623-8074